


## Technical data

Voltage class	M
Standard length	4 • 6 m
Air consumption	100 l/min
Air pressure	5 bar
Duty cycle 60%	40 A
Air pressure switch	≥ 3.5 bar



# S-45

**EA 236**  
151.30.44

**TP 80**  
130.30.02

**BX 20**  
151.30.36

**BX 130**  
Pilot arc (per meter)

**BX 200**  
**BX 138**  
Control leads (per meter)

**PF 125**

**PR 105**  
146.54.02

**PR 110**  
146.30.02  
• Standard

**PR 106**  
146.54.04

**PD 102-10**  
146.30.10  
(40 A)

**PE 106**  
148.54.12

**PD 116-08**  
146.30.15  
(20÷30 A)  
• Standard

**PD 103-09**  
146.30.60  
(20÷40 A)

**PC 116**  
148.30.32

**CV 10**  
148.30.52

**CV 24**  
151.30.24

**QB 44**  
Cable assembly cover (per meter)

**PH 270** Cable assembly

**PH 121**  
Air and power cable

**BX 29**  
(for **PA 166**)


1/4 G

**PH 285**  
Air and power cable





**BW 73**

1/4 G

**PH 290**  
Cable assembly  
(for **PA 167**)



**CV 25**  
151.30.00



**FY 23 Central**  
190.54.02

S 30 complete torch	m	Adaptor
<b>PA 165</b>	6	1/4 G
<b>PA 166</b>	6	central
<b>PA 167</b>	4	1/4 G